

HP Designjet T790 ePrinter series

An easy plug-and-play large-format ePrinter.









So easy and intuitive, you'll love using it.

- Print to any HP Designjet printer without installing any drivers thanks to free HP ePrint & Share 1.
- Save time with accurate page previews, and discover the power of touch through its colour touchscreen that enables easy printing.
- Secure your investment: this HP ePrinter is Web-connected and easy to update. Software updates occur automatically, every six months.
- Create a print-ready PDF2 file at the same time you print with HP ePrint & Share 1.

Print high-quality results at fast speeds.

- Achieve high-quality results: the 6-ink system has matte and photo black, and grey to produce true neutral greys and a wide range of vivid colours on plain and glossy
- Produce fine detailed lines with 0.02 mm minimum line width³, and highly accurate drawings with innovative printhead technology and Original HP inks.
- · Get the job done quickly without sacrificing quality: print up to 2 A1 prints per minute in Economode.
- Print complex files as easily as simple ones with 8 GB virtual memory⁴.

Access and print files where the job takes you.

- Print TIFF, JPEG, and PDF⁵ files directly from your USB flash drive - no computer required.
- Walk up to your printer's touchscreen, access files on the Web, and print them with HP ePrint & Share 1.
- Select and share projects using the touchscreen thanks to HP ePrint & Share 1.
- Send plans directly to your office or the client site, even when you're on the go, and print remotely⁶ to any large-format HP Web-connected Designjet from your computer or mobile device.

ecohighlights

- eve paper with automatic print settings and two-roll configuration.

 ss ink wasted due to efficient installation and maintenance routing
- Free, convenient HP ink cartridge and printhead recycling 1
- Works with FSCTM 2 and PEFC certified HP papers 3 ENERGY STAR® qualified
 - Visit http://www.hp.com/recycle to see how to participate and for HP Planet Partners programme
 - $2_{\text{Trademark license code FSC-C017543.}}$

- 1 HP ePrint & Share is a free Web-printing solution that lets you automatically manage content online. It requires an Internet connection. Download ePrint & Share: www.hp.com/go/eprintandshare
- 2 Requires AutoCAD plug-in.
- 3 $_{Using\ HP\text{-}GL/2}$.
- 4 Based on 640 MB RAM.
- $5\,_{PDF}$ files only available with PostScript accessory (optional accessory to be purchased separately) or buying PS versions
- 6 Remote Printing will be available by end of 2011.





















т	F	$\overline{}$	Н	N	110	\sim	Δ	П	S	P	F	C	ΙFΙ	(Δ	ΤI	0	N	١S

Storage humidity

0 to 95% RH

Print Line drawings	T790 610mm: 32 sec/page; T790 610mm PostScript: 32 sec/page; T790
	1118mm: 28 sec/page; T790 1118mm PostScript: 28 sec/page; 37 m²/hr on coaled media
Colour images	3/ m²/hr on coated media 2.8 m²/hr on glossy media
Print resolution	Up to 2400 x 1200 optimised dpi from 1200 x 1200 input dpi and
Nargins (top x bottom x left x right)	Optimisation For Photo Paper selected Roll: 5 x 5 x 5 x 5 mm
vidigins (lop x bolloni x len x rigili)	Sheet: 5 x 17 x 5 x 5 mm
echnology	HP Thermal Inkjet
nk types	Dye-based (C, G, M, pK, Y); pigment-based (mK)
nk colours nk drop	6 (cyan, grey, magenta, matte black, photo black, yellow) 6 pl (C, G, M, pK); 9 pl (mK, Y)
ine accuracy	+/- 0.1%
Minimum line width	0.02 mm (HP-GL/2 addressable)
Guaranteed minimum line width	0.06 mm (ISO/IEC 13660:2001(E))
Maximum print length Maximum optical density	91 m 2.15 maximum black optical density (6 L*min)
Media	2.13 maximum black objects actionly (o E min)
Handling	Sheet feed; roll feed; automatic cutter
lýpes	Bond and coated paper (bond, coated, heavyweight coated, super heavyweigh plus matte, coloured); technical paper (natural tracing, translucent bond, vellum) film (clear, matte, polyester); photographic paper (satin, gloss, semi-gloss, matte, high-gloss); backlit, self-adhesive (two-view cling, indoor paper, polypropylene, viryl)
Weight Size	60 to 328 g/m ² 1790 610mm: 210 x 279 to 610 x 1676 mm; 1790 610mm PostScript: 210 x
	279 to 610 \times 1676 mm; T790 1118mm: 210 \times 279 to 1118 \times 1676 mm; T790 1118mm PostScript: 210 \times 279 to 1118 \times 1676 mm;
hickness Memory	Up to 0.8 mm
itandard	8 GB (virtual)
Hard disk	T790 610mm: Optional, 160 GB (available with PostScript Upgrade); T790 610mm PostScript: Standard, 160 GB; T790 1118mm: Optional, 160 GB (available with PostScript Upgrade); T790 1118mm PostScript: Standard, 160 GB;
Connectivity nterfaces (standard)	Fast Ethernet (100Base-T); Hi-Speed USB 2.0; EIO Jetdirect accessory slot
nterfaces (optional)	Compatible HP Jetdirect print servers
Print languages (standard) Print languages (optional)	T790 610mm: HP.GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI; T790 610mm PostScript: Adobe® PostScript® 3; Adobe® PDF 1.7, HP.GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI; T790 1118mm: HP.GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI; T790 1118mm PostScript: Adobe® PostScript® 3; Adobe® PDF 1.7, HP.GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI; Adobe® PostScript® 3; Adobe® PDF 1.7
Drivers included	T790 610mm: HP-GL/2, HP-RTL drivers for Windows® (optimised for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; T790 610mm PostScript HP-GL/2, HP-RTL drivers for Windows® (optimised for AutoCAD 2000 and higher); PostScript® Windows®, Linux, and Mac drivers; T790 1118mm: HP-GL/2, HP-RTL drivers for Windows® (optimised for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; T790 1118mm PostScript: HP-GL/2 HP-RTL drivers for Windows® (optimised for AutoCAD 2000 and higher); PostScript® Windows®, Linux, and Mac drivers;
Recommended system requirements	
Mac Windows	Mac OS X v10.5: PowerPC G4, G5, or Intel® Core processor; 1 GB RAM; 2 G available hard disk space; Mac OS X v10.6: Mac computer with Intel® Core processor; 2 GB RAM; 4 GB available hard disk space Microsoft® Windows® 7: 32-bit (x86) or 64-bit (x64) processor (1 GHz); 2 GB
	RAM (32-bit) or 4 GB RAM (64-bit); 4 GB available hard disk space; Windows Vista® Ultimate, Business/Home Premium: 32-bit (x86) or 64-bit (x64) processo (1 GHz); 2 GB RAM; 4 GB available hard disk space; Windows® XP Professional/Home (SP2 or higher): Intel® Pentium® family or AMD K6™/Athlon™/Duron™ family (1 GHz); 1 GB RAM; 2 GB available hard disk space
Dimensions (w x d x h)	1790 610mm: 1262 x 702 x 1050 mm; 1790 610mm PostScript: 1262 x 702 x
	1050 mm; 1790 1118mm: $1770 \times 701 \times 1050$ mm; 1790 1118mm PostScript: $1770 \times 701 \times 1050$ mm;
Shipping	1790 610mm: 1440 x 766 x 770 mm; 1790 610mm Post Script: 1440 x 766 x 770 mm; 1790 1118mm Post Script: 1930 x 766 x 770 mm; 1790 1118mm Post Script: 1930 x 766 x 770 mm;
Veight	
Printer	T790 610mm: 60 kg; T790 610mm PostScript: 60 kg; T790 1118mm: 81.6 kg; T790 1118mm PostScript: 81.6 kg; T790 1118mm PostScript: 81.6 kg;
Shipping	T790 610mm: 77 kg; T790 610mm PostScript: 77 kg; T790 1118mm: 103 kg; T790 1118mm PostScript: 103 kg;
What's in the box	
CR647A	HP Designjet T790 ePrinter; printheads; introductory ink cartridges; spindle; quie reference guide; setup poster; startup software; power cord
CR648A	HP Designjet T790 PostScript ePrinter; printheads; introductory ink cartridges;
CR649A	spindle; quick reference guide; setup poster; startup software; power cord HP Designjet T790 ePrinter; printheads; introductory ink cartridges; printer stance
CR650A	spindle; quick reference guide; setup poster; startup software; power cord HP Designjet T790 PostScript ePrinter; printheads; introductory ink cartridges; printer stand; spindle; quick reference guide; setup poster; startup software;
- Comment of the comment	power cord
nvironmental ranges	
	5 to 40°C
Environmental ranges Operating Temperature Storage temperature	5 to 40°C -25 to 55°C

Acoustic									
Sound Pressure	46 dB(A); 29 dB(A) standby								
Sound Power	6.3 B(A); 4.4 B(A) standby								
Power Consumption									
Maximum	< 120 watts (active), < 27 watts (standby), < 7 watts / < 25 watts with embedded Digital Front End (sleep), 0.1 watts (off)								
Power requirements	Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max								
Certification									
Safety	EU (LVD and EN 60950-1 compliant); Russia (GOST)								
Electromagnetic	Compliant with Class B requirements EU (EMC Directive)								
Environmental	Energy Star; WEEE; EU RoHS; REACH; EuP; FEMP								
ENERGY STAR	ENERGY STAR® qualified								
Warranty									
	One-year limited hardware warranty. Warranty and support options vary by product, country and local legal requirements.								

ORDERING INFO	DRMATION
Product	
CR647A	HP Designjet T790 610mm ePrinter
CR648A	HP Designjet T790 610mm PostScript ePrinter
CR649A	HP Designjet T790 1118mm ePrinter
CR650A	HP Designjet T790 1118mm PostScript ePrinter
Accessories	
CN500B	HP Designjet PostScript Upgrade Kit
CQ783A	HP Designjet T7xx 24-in Spindle
Q6709A	HP Designjet 1118mm Roll Feed Spindle
Q6663A	HP Designjet T/Z 24-in Stand
CQ654A	HP Designjet HD Scanner
CN501A	HP Designjet External Hard Disk
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server
Ink supplies	
C9380A	HP 72 Gray and Photo Black Printhead
C9383A	HP 72 Magenta and Cyan Printhead
C9384A	HP 72 Matte Black and Yellow Printhead
C9397A	HP 72 69-ml Photo Black Ink Cartridge
C9398A	HP 72 69-ml Cyan Ink Cartridge
C9399A	HP 72 69-ml Magenta Ink Cartridge
C9400A	HP 72 69-ml Yellow Ink Cartridge
C9401A	HP 72 69-ml Grey Ink Cartridge
C9403A	HP 72 130-ml Matte Black Ink Cartridge
C9370A	HP 72 130-ml Photo Black Ink Cartridge
C9371A	HP 72 130-ml Cyan Ink Cartridge
C9372A	HP 72 130-ml Magenta Ink Cartridge
C9373A	HP 72 130-ml Yellow Ink Cartridge
C9374A	HP 72 130-ml Grey Ink Cartridge
Media supplies	
C6030C	HP Heavyweight Coated Paper-914 mm x 30.5 m (36 in x 100 ft)
Q1397A	HP Universal Bond Paper-914 mm x 45.7 m (36 in x 150 ft)
CG891A	HP Recycled Bond Paper-1067 mm x 45.7 m (42 in x 150 ft)
Service & support	
T790 610mm/ T790	HP596E HP 3 year Next Business Day Designjet T790-24inch Hardware Support
610mm PostScript	HP601E HP 4 year Next Business Day Designjet T790-24inch Hardware Support
	HP602E HP 5 year Next Business Day Designjet T790-24inch Hardware Support HP598E HP 3 year 4 hour 13x5 Designjet T790-24inch Hardware Support
	HP993PE HP 1 year Post Warranty Next Business Day Designjet T790-24inch Hardware Support
	HP994PE HP 2 year Post Warranty Next Business Day Designjet T790-24inch Hardware Support
	HP997PE HP 1 year Post Warranty 4 hour 13x5 Designjet T790-24inch Hardware Support
T790 1118mm/ T790	HP998E HP 3 year Next Business Day Designjet T790-44inch Hardware Support
1118mm PostScript	HQ009E HP 4 year Next Business Day Designjet T790-44inch Hardware Support
	HQ003E HP 5 year Next Business Day Designjet T790-44inch Hardware Support
	HP999E HP 3 year 4 hour 13x5 Designjet T790-44inch Hardware Support HQ015PE HP 1 year Post Warranty Next Business Day Designjet T790-44inch Hardware Support
	HQ013PE HP 2 year Post Warranty Next Business Day Designjet 1790-44inch Hardware Support
	HQ016PE HP 1 year Post Warranty 4 hour 13x5 Designjet T790-44inch Hardware Support
C	

Count on dependable support to create the best image possible. We can help you enhance your printing and imaging environment, protect your IT investment, and grow your business—with expert support that's affordable, personal, and tailored to your needs through HP Care Pack Services.

For more HP Large Format Media substrates and sizes please visit us online at: http://www.hp.com/go/designjet/supplies

For more information, visit our website at http://www.hp.com

© Copyright 2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA3-3938EEE Published in EMEA March 2011